



Kenflex™ Products

FLEXIBLE CONNECTOR

Kenflex Vinlon Flexible Connector is a laminated construction of top and bottom piles of vinyl, which is specially formulated for, prolonged outdoor weathering and provides superior dimensional stability & ultraviolet resistance.

Kenflex Vinlon Flexible Connector also qualifies for membranes in shelters & structures where dimensional stability & strength retention in prolonged outdoor exposure are essential requirements.

Brand	Kenflex
<u>Fabric Properties</u>	
Backing	Polyester/Vinyl
Coating	PVC
Weight	600 grams per sq meter
Colour	Glossy Black
Sizes	6" & 8" (W) x150ft (L)
Tensile Strength	
Warp	300 lbs per inch
Filling	300 lbs per inch
Heat Resistance	
	250°F intermittent
	180°F constant
Temperature Range	
Min.	- 30°C
Max.	80°C Intermittent
	70°C Continuous
Features	Self extinguishing, Highly Flexible, Low smoke, Lasting High Strength, Waterproof & Mildew Resistant, Heat, Cold & Abrasion Resistant, Age, Fade, Stain & Dirt Resistant, Flame Retardant.



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.