



# Kenflex<sup>TM</sup> Products

---

## FLEXIBLE CONNECTOR

---

**Kenflex Red Silicone Rubber Flexible Connector** is designed to give flexibility in applications where there is continuous movement, elevated temperature and exposure to harsh environments.

<b>Brand</b>	<b>Kenflex</b>
<b><u>Fabric Properties</u></b>	
<b>Backing</b>	<b>Glassfibre</b>
<b>Coating</b>	<b>Single sided Silicone Rubber</b>
<b>Weight</b>	<b>1600 gsm ( Nominal)</b>
<b>Thickness</b>	<b>2.2mm</b>
<b>Colour</b>	<b>Red</b>
<b>Sizes</b>	<b>8" to 12"width x 30m (L)</b>
<b>Tensile Strength</b>	
<b>Warp</b>	<b>1156 N/cm</b>
<b>Weft</b>	<b>480 N/cm</b>



<b>Operating Temperature.</b>	
<b>Basic Fabric</b>	<b>550°C</b>
<b>Surface Coating</b>	<b>250°C for 2 hr</b>

<b>Fire Standard</b>	<b>BS 476 Part 6 &amp; 7</b>
<b>Features</b>	<b>Water &amp; Oil resistant, Flame retardant, Low smoke developed, Flexible, Easily sewn, Good weathering</b>



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.