



Kenflex™ Products

ACCESS DOOR

Kenflex Access Doors are designed to provide quick and easy access to fire, smoke and volume control dampers, coils, filters, controls and other equipment mounted within air conditioning equipment or ductwork systems. The range of four sizes of rectangular access doors have been carefully selected to meet all requirements from single handed access to head and shoulder entry.

Brand **Kenflex**

Model **AD**

Material

Frame Seamless one-piece 0.8mm galvanised mild steel
Door Outer panel 0.8mm galvanized mild-steel
Inner panel 0.55mm galvanized mild steel
Insulation 25mm thick fiberglass
Gasket One piece moulded PVC
Fasteners Camlocks, zinc plated

Colour **Aluminium**

Standard **AD- S (10 pcs/ctn)**
Packaging **AD- M (10 pcs/ctn)**
AD- L (5 pcs/ctn)
AD- XL (5 pcs/ctn)

Sizes mm/inch - 148mm x 238mm (6"x 9.5")
- 240mm x 375mm (9.5"x15")
- 365mm x 500mm (14.5"x 20")
- 500mm x 649mm (20"x 26")

Features **Door is Two, Die-Formed and Seamless Panels in a Sandwich construction, Frame is Die-Formed and seamless, Progressive Cam and Lock Fastening.**



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.