



Kenflex™ Products

SEALANT

Kenflex Acrylic Sealant is for sealing metal/metal joints, particularly in air conditioning ductwork systems. The product is almost odor free and is not corrosive towards metals. After application the product forms a tough rubber by evaporation of water from the sealant. It prevents air and moisture from passing through cracks & joints.

Model		Kenflex
Colour		Grey
Form		Gunnable paste
Weight per litre		1.6kg
Composition		Synthetic polymers
Packaging		24 tubes per carton 300ml per tube
Average volatile	non-	82% by weight
Shelf Life		As least 12 months
Storage		+ 5°C to + 25°C
Cure time		Touch- 30 mins Through – 24 hours
Service Temp.		0°C to 70°C
Application Temp.		+ 5°C to + 40°C
Fire Standard		BS 476 Part 5 – Not easily ignitable
Features		Excellent durability and weather resistance, interior and exterior use, safe and easy application, good joint movement accommodation, good crack filling properties, can be over-painted



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.