



# Kenflex<sup>TM</sup> Products

---

## GASKET

---

**Kenflex Foam Tape** is a high quality closed cell gasket. It is ideally suited to forming permanent air and weather tight joints between sections of flanged ductwork, air handling unit panels, builders work openings and similar joint sealing applications. It is supplied in single rolls on silicone coated release paper for ease of application.

<b>Brand</b>	<b>Kenflex</b>
<b>Material</b>	<b>Nitrile Foam</b>
<b>Density</b>	<b>70-90 kg/m<sup>3</sup></b>
<b>Colour</b>	<b>Black</b>
<b>Sizes</b>	<b>13mm (W) x 6mm (Thk) x 7.5m (L) 19mm (W) x 6mm (Thk) x 7.5m (L)</b>
<b>Thermal Conductivity @Mean Temp. 20°C</b>	<b>0.28 Btu.in/hr/ft<sup>2</sup> F 0.038 W/m°C (0.0328Kcal/mh°C)</b>
<b>Temperature Limits</b>	<b>-40°C to + 105°C</b>
<b>Fire Resistance</b>	<b>Self Extinguishing</b>
<b>Toxicity</b>	<b>3.95</b>
<b>Water Absorption</b>	<b>3.85 (%W/W)</b>
<b>Mildew Resistance</b>	<b>No fungal growth</b>
<b>Weather Resistance</b>	<b>Good</b>
<b>UV Resistance</b>	<b>Good</b>
<b>Ozone Resistance</b>	<b>Excellent</b>
<b>Chemical Resistance</b>	<b>Good</b>
<b>Odour</b>	<b>Negligible</b>
<b>Flexibility</b>	<b>Excellent</b>
<b>Coating with release paper</b>	<b>Adhesive, tested OK</b>
<b>Fire Standard</b>	<b>ASTM D 635-98 – Rate of Burning and/or Extent and Time of Burning of Plastics in a Horizontal Position</b>
<b>Features</b>	<b>Under temperature 80°C &amp; 500hrs Excellent water resistance, Extreme flexibility, High Thermal resistance.</b>



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.