



KenflexTM Products

GLASS TAPE

Kenflex Glass Tape is specially developed for high temperature thermal insulation applications. These high quality tapes are produced from closely woven lofty yarns enabling thick tapes to be produced, which retain a high degree of softness and flexibility. It is most suitable as a high temperature gasket for Duct Flanges.

Brand	Kenflex
Model	Colan
Material	Woven lofty yarns
Colour	Off white
Sizes	20mm(W) x 3mm(Thk) x 30m(L) 40mm(W) x 3mm(Thk) x 30m(L)
Weight	1.3 kg /roll for 20mm 2.6 Kg/roll for 40mm
Low Thermal Conductivity	Approximately 0.05W/mK
Temperature	Up to 600°c
Fire Standard	BS 476 Part 6 & 7
Features	Inorganic, sterile and incombustible. Resistant to oils, solvents and most chemicals but direct contact with live steam should be avoided.
Applications	Fire-resistant curtains, protective clothing, controlled cooling of castings, insulation of gas and steam turbines, welding curtains, insulation linings, wrapping of exhausts flange jointing with openings for bolts, radiant heat shields.



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.