



# Kenflex<sup>TM</sup> Products

---

## FLEXIBLE CONNECTOR

---

**Kenflex Silcona Flexible Connector** is a premium fabric and is ideally recommended for use in high temperature applications. Most suitable for use on high pressure heating and Air-conditioning system.

<b>Brand</b>	<b>Kenflex</b>
<b><u>Fabric Properties</u></b>	
<b>Backing</b>	<b>Glassfibre</b>
<b>Coating</b>	<b>Silicona</b>
<b>Weight</b>	<b>500 grams per sq meter</b>
<b>Colour</b>	<b>Silver Grey</b>
<b>Sizes</b>	<b>6" &amp; 8" (W) x100ft (L)</b>
<b>Tensile Strength</b>	
<b>Warp</b>	<b>285.5 lbs per inch</b>
<b>Weft</b>	<b>228.5 lbs per inch</b>
<b>Tear Strength</b>	
<b>Warp</b>	<b>130.42 lbs per sq. inch</b>
<b>Weft</b>	<b>157.75 lbs per sq. inch</b>
<b>Heat Resistance</b>	<b>Incombustible, M.O., 400 °C 2/H</b>
<b>Temperature Range</b>	
<b>Min.</b>	<b>- 40°C</b>
<b>Max.</b>	<b>310°C Intermittent 280°C Continuous</b>
<b>Fire Standard</b>	<b>BS 476 Part 6 &amp; 7</b>
<b>Features</b>	<b>Resistant to ozone, fading, weathering, abrasion, acids and most chemicals, Extremely high flame retardant, Resistance to tear and puncture.</b>



Every effort is made to ensure that the information contained in our literature, drawings and correspondence is accurate, but no warranty is given in this respect and the Company shall not be liable as a result of any inaccuracy. The Company reserves the right to alter at any time without prior notice, the design, specification, packaging or price of any article and without incurring any obligation. All quantities, weight, etc., subject to normal commercial tolerance.